

PROPUCK XENON

Integrated / Linkable Puck Lights

PP-XX-1

FEATURES

- Surface or recessed mount (not for recessed installation in ceilings or walls)
- 120V, 20W Xenon lamp
- 2900°K
- 7,000-hour rated lamp life
- Link a maximum of 450W
- Dimmable with standard Incandescent dimmer (must meet minimum load of dimmer)
- Complete with lamp, flange and clips for recessing, screws for surface mount and mini strain reliefs
- Metal honeycomb lens included, additional accessory lenses available
- UL listed for a portable and hardwire compartment; C-UL when used with C-UL strain relief



HOUSING

- Diecast aluminum construction for durability and excellent heat dissipation
- Integral mounting standoffs create an airgap between fixture and mounting surface, minimizing heat transfer in surface mount applications
- Internal terminal block included, no wire nuts or connectors needed
- Hardwire knockouts on sides and back, additional MC connectors available
- Installation requires SJT cord or similar (see below for CSL's PP-CRD cord options)
- See www.csllighting.com for current photometric data


FINISHES

- White (WT)
- Satin Aluminum (SA)
- Bronze (BZ)
- Black (BK)

Project notes:




ACCESSORY LENSES



0-19
Prismatic
Spread Lens



0-16
Mini Prismatic
Lens



0-18
Linear
Spread Lens

ACCESSORIES



PP-CON
Flex conduit connector.
Fits up to 1/2" flex
conduit. Side knockout
only



INVWC3
Low-profile wiring
compartment
4"l x 2 1/8"w x 1"h



PP-CRD-XX
Black linking cord, 10'
PP-CRD-XX-100
Black linking cord, 100'

XX = two digit finish code. Black (BK)
or White (WT)



PP-PLG-XX
Black cord with plug, 6'

XX = two digit finish code.
Black (BK) or White (WT)



A Division of Troy-CSL

14508 Nelson Avenue City of Industry, CA 91744 Tel 626-336-4511 Fax 626-336-4266 www.csllighting.com

Rev 063016