

ELECTRIC SELF-CLEAN RANGE

RVER330-5B – 30" WIDE



Features and Functions

- Wide variety of surface element sizes and wattages, including a fifth element
 - Left front – 8 1/2" 2,000-watt dual element
 - Left rear – 6 1/2" 1,200-watt single element
 - Center – 12" 3,200-watt triple element
 - Right front – 6 1/2" 1,200-watt single element
 - Right rear – 8 1/2" 2,000-watt dual element
- QuickCook™ Surface Elements utilize ribbon technology to reach full power in about three seconds
- **Exclusive** – largest oven cavity in the industry
 - 4.7 cu. ft. overall
 - 4.1 cu. ft. measured to AHAM Standards
(See specifications chart for oven interior dimensions)
- High performance cooking modes include Bake, Convection Bake, TruConvec™ Convection Cooking, Convection Roast, Hi Broil, Medium Broil, Low Broil, Convection Broil, Convection Dehydrate, and Convection Defrost
- **Exclusive** – Patented Vari-Speed Dual Flow™ Convection System has the largest convection fan in the industry; the 8 1/2" fan works bi-directionally for maximum airflow and excellent cooking results
- Concealed 10-pass dual-bake element provides precise temperature control

- 10-pass broiler with heat reflector provides superior broiling performance
- Rapid Ready™ Preheat provides superfast preheating
- Oven has six porcelain-coated rack supports and comes standard with one TruGlide™ full extension oven rack and two standard racks
- Halogen oven lighting provides excellent visibility throughout oven cavity
- Shipped standard with Island trim

Easy Operation and Cleanup

- Extremely large self-clean convection oven
- Strong, wear-resistant glass ceramic surface with stainless steel frame offers excellent cleanability
- Durable metal die-cast knobs with child-proof, push-to-turn safety feature
- Customer-removable knobs for easy cleaning

Installation Accessories

- 6" high backguard (RD30BG6)
- High shelf (RD30HS24)
- Countertop side trim (P24CST)
- Countertop rear trim (P30CRT)
- Curb base and custom curb base front (P30CBF4)

Finishes

- Available in Stainless Steel (SS), Black (BK), and White (WH)



Warranty Highlights

- Three-year full – complete product
- Ninety-day full – cosmetic parts such as glass, painted items, and decorative items
- Lifetime limited – stainless steel exterior
- Ten-year limited – porcelain oven
- Five-year limited – surface/tube burners



30" Wide Electric Range
(Shown with optional 6" H. backguard)

DESCRIPTION	ELECTRIC SELF-CLEAN 30" WIDE RANGE
	RVER330-5B
Overall Width	29 7/8" (75.9 cm)
Overall Height	To top of side trim – 35 7/8" (91.1 cm) minimum; 37" (94.0 cm) maximum Legs adjust – 1 1/8" (2.9 cm)
Overall Depth from Rear	To front of side panel – 25" (63.5 cm) To front of door – 25 3/4" (65.4 cm) To front of control panel – 27 1/8" (68.9 cm) To end of knobs – 29" (73.7 cm)
Additions to Overall Height	To top of island trim – add 0" (0.0 cm) To top of 6" h. backguard – add 6" (15.2 cm) To top of high shelf – add 18 3/16" (46.2 cm)
Electrical Requirements	240-208 VAC 60 Hz electrical connection box on product, connect with locally supplied 3-wire, flexible cord or "pigtail" rated 40 amp. 125-250 VAC minimum. Cord must be agency approved for use with household electric ranges.
Maximum Wattage/ Amp Usage	240V – 15,200 watts – 63.3 amps 208V – 11,400 watts – 54.8 amps
Surface Element Rating	Left Front – 2,000 watts Left Rear – 1,200 watts Center – 3,200 watts Right Front – 1,200 watts Right Rear – 2,000 watts
Oven Interior Width	25 5/16" (64.6 cm)
Oven Interior Height	16 1/2" (41.9 cm)
Oven Interior Depth	Overall – 19 1/2" (49.5 cm) AHAM* – 16 13/16" (42.7 cm)
Oven Volume	Overall – 4.7 cu. ft. AHAM* – 4.1 cu. ft.
Approximate Shipping Weight	424 lb. (190.8 kg)

*The AHAM standard for measuring oven capacity subtracts the doorplug and convection baffle dimension from the total oven volume.



Viking Range, LLC | 1-888-845-4641 or 662-455-1200

For detailed product information, model numbers, or to request a quote visit vikingrange.com

© 2013 Viking Range, LLC | Specifications subject to change without notice.